

This LED beacon has unique LED reflectors which provide a focused signal for superior brightness. The lens construction provides an excellent horizontal spread for easy identification of optical signal. The light has 3 flash patterns plus 4 simulated rotating patterns which provide plenty of lighting options. Low amp draw and bright output make it the ideal beacon for everyday use.



Available in:

Amber - T330012406

White - T330012407

Magnetic Magnet base	4H Charge pendant Charge	6H Discharging time Discharging	Shocks resistant Approval	ECE R65 Approval	EMC R10 Approval	IP67 IP Rating	12-24 V Power Supply	+65°C -40°C Operating Temperature
-------------------------	--------------------------------	---------------------------------------	------------------------------	---------------------	---------------------	-------------------	-------------------------	---

Product Information

Power Consumption	Current/Voltage	SMD	LED Qty	Colour Temperature	Compliance
18 w	0.75 A @ 24 V	3 535	10	590-595 K	R65

Charging Parameters

Charging Interface	Electric Core	Capacity	Charging Voltage	Charging Current	Charge Pendant	Discharging Time
DC5.5/2.1	Double Section 18 650 Lithium Ion	7.4 V 2 600 mAh	12 V	700 mA	4 H	6 H

State	Electric Quantity	Indicator Light
Charging Status	0-30%	●
	30-99%	●
	100%	●
Discharge	70-100%	●
	30-70%	●
	10-30%	●
	10% below	Red flashing lights

